



range introduction

The simple, clean styling of Aspect is both classic and contemporary, so it looks at home anywhere, in almost any kind of environment where style and quality are important. The profile is just 4mm slim, so it's discreet, as well as stylish, while the concealed screws leave an elegant frontplate, making it more attractive still.

In addition to impressive looks, with Aspect comes unrivalled safety. Utilising MK's 3-pin operated safety shutter, that prevents misuse and unsafe access to live circuitry, Aspect offers the user the peace of mind and comfort that they have the safest range of wiring devices available installed in their surroundings.

Echo™ is an innovative range of entirely wireless, batteryless and self powered switches, only available from MK Electric and in finishes to complement the Aspect range. Please see page 26 for details.

feature benefits

Slim profile 'screwless' front plates of only 4mm

Provide a clean and flawless look that complements the décor of the finest interiors

Patented spring clip design

Ensures positive earth connection of the frontplate and end user safety

Total safety

3-pin operated "child resistant shutter system", which is designed to inhibit access to the electricity supply, unless all 3 pins of a standard British 13 Amp plug are in position

6 standard high quality finishes with the option for custom design service

Enables Aspect to provide a stylish finish to any new décor

SUPERMOON
Powering modern work and life

Order at 訂貨熱線 :

香港批發 / 分銷 T (852) 2781 2855

澳門批發 / 分銷 T (853) 2822 2751

工程 / 商業項目 T (852) 2691 9166

E enquiry@supermoon.hk

www.supermoon.hk

technical hotline +44 (0)1268 563720

decorative | wiring devices

MATCHING METAL ROCKER SWITCHES

DOUBLE POLE SWITCHING

SIX HIGH QUALITY FINISHES TO CHOOSE FROM

CHOICE OF BLACK OR WHITE INSERTS ON MOST FINISHES
Provide impact resistance in any environment

STYLISH SLIM-LINE DESIGN
Frontplate profile only 4mm

PATENTED SPRING CLIP FOR POSITIVE EARTHING

CORROSION RESISTANT SURFACE TREATED FRAME

SCREWDRIVER GUIDING RAMP

3-PIN "CHILD RESISTANT SHUTTER SYSTEM"
Designed to inhibit access to the electricity supply, unless all 3 pins of a standard British 13 Amp plug are in position

As well as a wide choice of finishes new MK Aspect is available in a range of outlets for interactive and digital TV, IT and telecomms services. There are reliable and effective dimmer switches, and a comprehensive range of modular switches – all simple to install.

Terminal screws are backed out and captive Terminals are upwards facing to make installation easier.

Funnel entrance to terminals.

Clear terminal markings for easy identification.



Switchsocket Outlets

1 GANG DP DUAL EARTH 13 AMP	1 GANG DP WITH NEON DUAL EARTH 13 AMP	2 GANG DP DUAL EARTH 13 AMP	2 GANG DP WITH NEON DUAL EARTH 13 AMP	1 GANG DP ROUND PIN 5 AMP	1 GANG DP ROUND PIN 15 AMP
-----------------------------------	--	-----------------------------------	--	---------------------------------	----------------------------------



FINISHES

BRUSHED STAINLESS STEEL	STD	K24357 BSS W	K24657 BSS W	K24347 BSS W	K24647 BSS W	K24382 BSS W	K24383 BSS W
	OPT	K24357 BSS B	K24657 BSS B	K24347 BSS B	K24647 BSS B	K24382 BSS B	K24383 BSS B
LACQUERED BRUSHED STEEL	OPT	K24357 LBS W		K24347 LBS W			K24383 LBS W
	STD	K24357 LBS B		K24347 LBS B			K24383 LBS B
POLISHED BRASS	OPT	K24357 PBR W	K24657 PBR W	K24347 PBR W	K24647 PBR W	K24382 PBR W	K24383 PBR W
	STD	K24357 PBR B	K24657 PBR B	K24347 PBR B	K24647 PBR B	K24382 PBR B	K24383 PBR B
POLISHED CHROME	OPT	K24357 POC W	K24657 POC W	K24347 POC W	K24647 POC W	K24382 POC W	K24383 POC W
	STD	K24357 POC B	K24657 POC B	K24347 POC B	K24647 POC B	K24382 POC B	K24383 POC B
WHITE	STD	K24357 WHI W	K24657 WHI W	K24347 WHI W	K24647 WHI W	K24382 WHI W	K24383 WHI W
CHARCOAL	STD	K24357 CHA B	K24657 CHA B	K24347 CHA B	K24647 CHA B	K24382 CHA B	K24383 CHA B

- W** White Inserts
B Black Inserts
STD Standard Black or White
STD White
OPT Option Black or White
OPT White

MOUNTING BOXES:
 FLUSH 35mm: 866 ZIC
 FLUSH 46mm: 877 ZIC
 (for extra wiring space)

DIMENSIONS:
 86 x 86mm

FIXING CENTRES:
 60.3mm

BS 1363 Pt 2: 1995

MOUNTING BOXES:
 FLUSH 35mm: 866 ZIC
 FLUSH 46mm: 877 ZIC
 (for extra wiring space)

DIMENSIONS:
 86 x 86mm

FIXING CENTRES:
 60.3mm

BS 1363 Pt 2: 1995

Neon is only available in white or black rocker.

MOUNTING BOXES:
 FLUSH 35mm: 886 ZIC
 FLUSH 47mm: 878 ZIC
 (for extra wiring space)

DIMENSIONS:
 86 x 146mm

FIXING CENTRES:
 120.6mm

BS 1363 Pt 2: 1995

MOUNTING BOXES:
 FLUSH 35mm: 886 ZIC
 FLUSH 47mm: 878 ZIC
 (for extra wiring space)

DIMENSIONS:
 86 x 146mm

FIXING CENTRES:
 120.6mm

BS 1363 Pt 2: 1995

Neon is only available in white or black rocker.

MOUNTING BOXES:
 FLUSH 35mm: 866 ZIC
 FLUSH 46mm: 877 ZIC
 (for extra wiring space)

DIMENSIONS:
 86 x 86mm

FIXING CENTRES:
 60.3mm

BS 546: 1950

MOUNTING BOXES:
 FLUSH 35mm: 866 ZIC
 FLUSH 46mm: 877 ZIC
 (for extra wiring space)

DIMENSIONS:
 86 x 86mm

FIXING CENTRES:
 60.3mm

BS 546: 1950

LEAD TIMES
 Please contact our Customer Services Department on: 01268 563000

Dual Earth: Fitted with two earth terminals to provide a double earth facility for use when installations require a high integrity protective connection as specified within BS 7671: 2008.

Dual Earth (see note box)

Dual Earth (see note box)

technical hotline +44 (0)1268 563720

decorative | wiring devices

Socket Outlets

 1 GANG
DUAL EARTH
13 AMP

 2 GANG
DUAL EARTH
13 AMP

 1 GANG
ROUND PIN
2 AMP

 1 GANG
ROUND PIN
5 AMP

 GERMAN
2P+E 1 GANG
16 AMP 250V
SHUTTERED
(NON UK)

K24780 BSS W K24780 BSS B	K24781 BSS W K24781 BSS B	K24380 BSS W K24380 BSS B	K24381 BSS W K24381 BSS B	K24182 BSS K5831 WHI K5831 BLK
			K24381 LBS W K24381 LBS B	K24182 LBS K5831 WHI K5831 BLK
K24780 PBR W K24780 PBR B	K24781 PBR W K24781 PBR B		K24381 PBR W K24381 PBR B	K24182 PBR K5831 WHI K5831 BLK
K24780 POC W K24780 POC B	K24781 POC W K24781 POC B		K24381 POC W K24381 POC B	K24182 POC K5831 WHI K5831 BLK
K24780 WHI W	K24781 WHI W	K24380 WHI W	K24381 WHI W	K24182 WHI K5831 WHI
K24780 CHA B	K24781 CHA B	K24380 CHA B	K24381 CHA B	K24182 CHA K5831 BLK

 MOUNTING BOXES:
FLUSH 35mm: 866 ZIC
FLUSH 46mm: 877 ZIC
(for extra wiring space)

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

BS 1363 Pt. 2: 1995

 MOUNTING BOXES:
FLUSH 35mm: 886 ZIC
FLUSH 47mm: 878 ZIC
(for extra wiring space)

 DIMENSIONS:
86 x 146mm

 FIXING CENTRES:
120.6mm

BS 1363 Pt. 2: 1995

 MOUNTING BOXES:
FLUSH 35mm: 866 ZIC
FLUSH 46mm: 877 ZIC
(for extra wiring space)

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

BS 546: 1950

 MOUNTING BOXES:
FLUSH 35mm: 866 ZIC
FLUSH 46mm: 877 ZIC
(for extra wiring space)

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

BS 546: 1950

 MOUNTING BOXES:
FLUSH 46mm: 877 ZIC

 DIMENSIONS:
86 x 86mm

IEC 60884-1: 2006

This is a modular product. The front plate (K24182) and socket (K5831) need to be ordered separately. Add appropriate suffix to the list numbers.

UNIVERSAL
SOCKET
1 GANG
16 AMP
(NON UK)

Shaver Supply Outlets

DUAL VOLTAGE
115/230V OUTPUT
220/240V
50/60Hz INPUT

Connection Units Switched

DP
13 AMP

DP
WITH NEON
13 AMP

DP WITH
NEON &
FLEX OUTLET
13 AMP

Connection Units Unswitched

WITH NEON
13 AMP

WITH NEON &
FLEX OUTLET
13 AMP



MODULAR
Order plate
and insert



FINISHES

BRUSHED STAINLESS STEEL	STD	K24331 BSS K4901 WHI K4901 BLK	K24709 BSS W K24709 BSS B	K24941 BSS W K24941 BSS B	K24961 BSS W K24961 BSS B	K24971 BSS W K24971 BSS B	K24958 BSS W K24958 BSS B	K24978 BSS W K24978 BSS B
	OPT							
LACQUERED BRUSHED STEEL	OPT	K24331 LBS K4901 WHI K4901 BLK	K24709 LBS W K24709 LBS B	K24941 LBS W K24941 LBS B	K24961 LBS W K24961 LBS B	K24971 LBS W K24971 LBS B	K24958 LBS W K24958 LBS B	K24978 LBS W K24978 LBS B
	STD							
POLISHED BRASS	OPT	K24331 PBR K4901 WHI K4901 BLK	K24709 PBR W K24709 PBR B	K24941 PBR W K24941 PBR B	K24961 PBR W K24961 PBR B	K24971 PBR W K24971 PBR B	K24958 PBR W K24958 PBR B	K24978 PBR W K24978 PBR B
	STD							
POLISHED CHROME	OPT	K24331 POC K4901 WHI K4901 BLK	K24709 POC W K24709 POC B	K24941 POC W K24941 POC B	K24961 POC W K24961 POC B	K24971 POC W K24971 POC B	K24958 POC W K24958 POC B	K24978 POC W K24978 POC B
	STD							
WHITE	STD	K24331 WHI K4901 WHI	K24709 WHI W	K24941 WHI W	K24961 WHI W	K24971 WHI W	K24958 WHI W	K24978 WHI W
CHARCOAL	STD	K24331 CHA K4901 BLK	K24709 CHA B	K24941 CHA B	K24961 CHA B	K24971 CHA B	K24958 CHA B	K24978 CHA B

MOUNTING BOXES: FLUSH: 878 ZIC

This design incorporates a double wound isolating transformer rated 20VA at 230 or 115 volts and meets BS EN 61558-2-5: 1996 making it safe for use in bathrooms.

MOUNTING BOXES:
FLUSH 35mm: 866 ZIC
FLUSH 46mm: 877 ZIC
(for extra wiring space)

DIMENSIONS:
86 x 86mm

BS 5733: 1995

Grid Plus frontplates, supplied with mounting frame. The Universal Socket does not incorporate an earth contact. Appliances needing earth connection (class 1 equipment) must NOT be used with this socket. The socket is intended for use with BS, USA and CEE plugs.

Insertion of a shaver plug automatically switches on by energising the primary side of the isolating transformer – removal automatically switches off. The transformer is protected against overload by an automatic solid state overload device with automatic resetting.

DIMENSIONS:
146 x 86mm

FIXING CENTRES:
120.6mm

BS EN 61558-2-5: 1998

MOUNTING BOXES:
FLUSH: 877 ZIC

All connection units are fitted with a 13 amp fuse (to BS 1362).

TERMINAL CAPACITY:
2 x 6mm² stranded (max)

DIMENSIONS:
86 x 86mm

FIXING CENTRES:
60.3mm

BS 1363-4: 1995

Neon is only available in white or black rocker.

LEAD TIMES
Please contact our Customer
Services Department on:
01268 563000

Matching metal capped fuse carriers are standard on all Aspect Connection Units (except Black and White).

technical hotline +44 (0)1268 563720

decorative | wiring devices

Switches

1 GANG SP 2 WAY 20 AMP	2 GANG SP 2 WAY 20 AMP	3 GANG SP 2 WAY 10 AMP	1 GANG SP 2 WAY 20 AMP WITH LARGE ROCKER	2 GANG SP 2 WAY 20 AMP WITH LARGE ROCKERS	1 GANG SP 2 WAY 20 AMP WITH WIDE ROCKER	1 GANG DP WITH NEON 32 AMP	1 GANG DP WITH NEON 50 AMP	3 POLE FAN ISOLATOR
------------------------------	------------------------------	------------------------------	--	---	---	----------------------------------	----------------------------------	------------------------

K24371 BSS W K24371 BSS B	K24372 BSS W K24372 BSS B	K24373 BSS W K24373 BSS B	K23471 BSS W K23471 BSS B	K23472 BSS W K23472 BSS B	K23473 BSS W K23473 BSS B	K24305 BSS W K24305 BSS B	K24336 BSS W K24336 BSS B	K24859 BSS W K24859 BSS B
K24371 LBS W K24371 LBS B	K24372 LBS W K24372 LBS B	K24373 LBS W K24373 LBS B	K23471 LBS W K23471 LBS B	K23472 LBS W K23472 LBS B		K24305 LBS W K24305 LBS B	K24336 LBS W K24336 LBS B	K24859 LBS W K24859 LBS B
K24371 PBR W K24371 PBR B	K24372 PBR W K24372 PBR B	K24373 PBR W K24373 PBR B				K24305 PBR W K24305 PBR B	K24336 PBR W K24336 PBR B	K24859 PBR W K24859 PBR B
K24371 POC W K24371 POC B	K24372 POC W K24372 POC B	K24373 POC W K24373 POC B	K23471 POC W K23471 POC B	K23472 POC W K23472 POC B	K23473 POC W K23473 POC B	K24305 POC W K24305 POC B	K24336 POC W K24336 POC B	K24859 POC W K24859 POC B
K24371 WHI W	K24372 WHI W	K24373 WHI W	K23471 WHI W	K23472 WHI W	K23473 WHI W	K24305 WHI W	K24336 WHI W	K24859 WHI W
K24371 CHA B	K24372 CHA B	K24373 CHA B				K24305 CHA B	K24336 CHA B	K24859 CHA B

MOUNTING BOXES:
FLUSH: 861 ZIC
TERMINAL CAPACITY:
2 x 6mm² Stranded
(max)
DIMENSIONS:
86 x 86mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 861 ZIC
TERMINAL CAPACITY:
2 x 6mm² Stranded
(max)
DIMENSIONS:
86 x 86mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 861 ZIC
DIMENSIONS:
86 x 86mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 861 ZIC
DIMENSIONS:
86 x 86mm
ROCKER
DIMENSIONS:
22 x 40mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 861 ZIC
DIMENSIONS:
86 x 86mm
ROCKER
DIMENSIONS:
22 x 40mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 861 ZIC
DIMENSIONS:
86 x 86mm
ROCKER
DIMENSIONS:
50 x 40mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 861 ZIC
DIMENSIONS:
86 x 86mm
ROCKER
DIMENSIONS:
22 x 40mm
FIXING CENTRES:
60.3mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 878 ZIC
DIMENSIONS:
86 x 146mm
FIXING CENTRES:
120.6mm
BS EN 60669-1: 2000

MOUNTING BOXES:
FLUSH: 861 ZIC
DIMENSIONS:
86 x 86mm
FIXING CENTRES:
60.3mm
BS EN 60947-3: 1992

Grid Plus Modular Frontplates

SUPPLIED WITH MOUNTING FRAME

1 MODULE

2 MODULE

3 MODULE

4 MODULE

6 MODULE

8 MODULE



FINISHES

BRUSHED STAINLESS STEEL	<input type="checkbox"/> STD <input type="checkbox"/> OPT	K24331 BSS	K24332 BSS	K24333 BSS	K24334 BSS	K24346 BSS	K24348 BSS
LACQUERED BRUSHED STEEL	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K24331 LBS	K24332 LBS	K24333 LBS	K24334 LBS	K24346 LBS	K24348 LBS
POLISHED BRASS	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K24331 PBR	K24332 PBR	K24333 PBR	K24334 PBR	K24346 PBR	K24348 PBR
POLISHED CHROME	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K24331 POC	K24332 POC	K24333 POC	K24334 POC	K24346 POC	K24348 POC
WHITE	<input type="checkbox"/> STD	K24331 WHI	K24332 WHI	K24333 WHI	K24334 WHI	K24346 WHI	K24348 WHI
CHARCOAL	<input type="checkbox"/> STD	K24331 CHA	K24332 CHA	K24333 CHA	K24334 CHA	K24346 CHA	K24348 CHA

- W** White Inserts
B Black Inserts
 STD Standard Black or White
 STD White
 OPT Option Black or White
 OPT White

MOUNTING BOX:
 FLUSH: 891 ALM
 DIMENSIONS:
 86 x 86mm
 BS 5733: 1995

MOUNTING BOX:
 FLUSH: 891 ALM
 DIMENSIONS:
 86 x 86mm
 BS 5733: 1995

MOUNTING BOX:
 FLUSH: 892 ALM
 DIMENSIONS:
 86 x 146mm
 BS 5733: 1995

MOUNTING BOX:
 FLUSH: 892 ALM
 DIMENSIONS:
 86 x 146mm
 BS 5733: 1995

MOUNTING BOX:
 FLUSH: 893 ALM
 DIMENSIONS:
 146 x 146mm
 BS 5733: 1995

MOUNTING BOX:
 FLUSH: 893 ALM
 DIMENSIONS:
 146 x 146mm
 BS 5733: 1995

technical hotline +44 (0)1268 563720

decorative | wiring devices

Toggle Switch Frontplates

SUPPLIED WITH MOUNTING FRAME

1 MODULE TOGGLE SWITCH FRONTPLATE	2 MODULE TOGGLE SWITCH FRONTPLATE	3 MODULE TOGGLE SWITCH FRONTPLATE	4 MODULE TOGGLE SWITCH FRONTPLATE
--	--	--	--

Toggle Switch Modules

20 AMP SP 1 WAY TOGGLE SWITCH	20 AMP SP 2 WAY TOGGLE SWITCH	20 AMP DP 1 WAY TOGGLE SWITCH	20 AMP INTERMEDIATE TOGGLE SWITCH
--	--	--	--

K24431 BSS	K24432 BSS	K24433 BSS	K24434 BSS	K14891 BSS	K14892 BSS	K14896 BSS	K14893 BSS
K24431 PBR	K24432 PBR	K24433 PBR	K24434 PBR	K14891 PBR	K14892 PBR	K14896 PBR	K14893 PBR
K24431 POC	K24432 POC	K24433 POC	K24434 POC	K14891 POC	K14892 POC	K14896 POC	K14893 POC
K24431 WHI	K24432 WHI	K24433 WHI	K24434 WHI	K14891 WHI	K14892 WHI	K14896 WHI	K14893 WHI
K24431 CHA	K24432 CHA	K24433 CHA	K24434 CHA				

MOUNTING BOX:
FLUSH: 891 ALM
DIMENSIONS:
86 x 86mm
BS 5733: 1995

MOUNTING BOX:
FLUSH: 891 ALM
DIMENSIONS:
86 x 86mm
BS 5733: 1995

MOUNTING BOX:
FLUSH: 892 ALM
DIMENSIONS:
86 x 146mm
BS 5733: 1995

MOUNTING BOX:
FLUSH: 892 ALM
DIMENSIONS:
86 x 146mm
BS 5733: 1995

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent and inductive loads.
BS EN 60669-1: 2000

Switch Modules 10 Amp

10 AMP
SP 1 WAY

10 AMP
SP 2 WAY

10 AMP
SP 2 WAY
PUSH SWITCH

10 AMP
SP 2 WAY
RED ROCKER
PUSH SWITCH

10 AMP
SP 2 WAY
BELL
PUSH SWITCH

10 AMP
SP 2 WAY
PRESS
PUSH SWITCH



FINISHES

BRUSHED STAINLESS STEEL	STD	K4881 BSS W	K4882 BSS W	K4885 BSS W	K4885 RED	K4885 B WHI	K4885 P WHI
	OPT	K4881 BSS B	K4882 BSS B	K4885 BSS B	K4885 RED B	K4885 B WHI B	K4885 P WHI B
LACQUERED BRUSHED STEEL	OPT	K4881 LBS W	K4882 LBS W	K4885 LBS W	K4885 RED	K4885 B WHI	K4885 P WHI
	STD	K4881 LBS B	K4882 LBS B	K4885 LBS B	K4885 RED B	K4885 B WHI B	K4885 P WHI B
POLISHED BRASS	OPT	K4881 PBR W	K4882 PBR W	K4885 PBR W	K4885 RED	K4885 B WHI	K4885 P WHI
	STD	K4881 PBR B	K4882 PBR B	K4885 PBR B	K4885 RED B	K4885 B WHI B	K4885 P WHI B
POLISHED CHROME	OPT	K4881 POC W	K4882 POC W	K4885 POC W	K4885 RED	K4885 B WHI	K4885 P WHI
	STD	K4881 POC B	K4882 POC B	K4885 POC B	K4885 RED B	K4885 B WHI B	K4885 P WHI B
WHITE	STD	K4881 WHI W	K4882 WHI W	K4885 WHI W	K4885 RED	K4885 B WHI	K4885 P WHI
CHARCOAL	STD	K4881 CHA B	K4882 CHA B	K4885 CHA B	K4885 RED B	K4885 B WHI B	K4885 P WHI B

W White Inserts
B Black Inserts
STD Standard Black or White
STD White
 Option Black or
OPT White

These switches do NOT have to be derated when used with fluorescent or inductive loads.
 BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.
 BS EN 60669-1: 2000

These switches do NOT have to be derated when used with inductive loads.
 Note: Push switches are not designed for fluorescent loads.
 BS EN 60669-1: 2000

These switches do NOT have to be derated when used with inductive loads.
 Note: Push switches are not designed for fluorescent loads.
 BS EN 60669-1: 2000

These switches do NOT have to be derated when used with inductive loads.
 Note: Push switches are not designed for fluorescent loads.
 BS EN 60669-1: 2000

These switches do NOT have to be derated when used with inductive loads.
 Note: Push switches are not designed for fluorescent loads.
 BS EN 60669-1: 2000

technical hotline +44 (0)1268 563720

decorative | wiring devices

Switch Modules 20 Amp

10 AMP DP 1 WAY	10 AMP 2 WAY CENTRE OFF RETRACTIVE PUSH	20 AMP SP 1 WAY	20 AMP SP 1 WAY WITH WINDOW	20 AMP SP 2 WAY	20 AMP SP 2 WAY WITH WINDOW
--------------------	---	--------------------	--------------------------------------	--------------------	--------------------------------------

K4981 BSS W K4981 BSS B	K4900 BSS W K4900 BSS B	K4891 BSS W K4891 BSS B	K4891 W WHI K4891 W BLK	K4892 BSS W K4892 BSS B	K4892 W WHI K4892 W BLK
	K4900 LBS W K4900 LBS B	K4891 LBS W K4891 LBS B	K4891 W WHI K4891 W BLK	K4892 LBS W K4892 LBS B	K4892 W WHI K4892 W BLK
K4981 PBR W K4981 PBR B	K4900 PBR W K4900 PBR B	K4891 PBR W K4891 PBR B	K4891 W WHI K4891 W BLK	K4892 PBR W K4892 PBR B	K4892 W WHI K4892 W BLK
K4981 POC W K4981 POC B	K4900 POC W K4900 POC B	K4891 POC W K4891 POC B	K4891 W WHI K4891 W BLK	K4892 POC W K4892 POC B	K4892 W WHI K4892 W BLK
K4981 WHI	K4900 WHI W	K4882 WHI W	K4891 W WHI	K4892 WHI W	K4892 W WHI
K4981 CHA B	K4900 CHA B	K4882 CHA B	K4891 W BLK	K4892 CHA B	K4892 W BLK

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with inductive loads.

Note: Push switches are not designed for fluorescent loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

Switch Modules

20 Amp DP 1 WAY WITH TEXT	20 Amp DP 1 WAY WITH NEON AND TEXT	20 AMP INTERMEDIATE	20 AMP INTERMEDIATE RED ROCKER	20 AMP SP 2 WAY & CENTRE OFF	20 AMP SP 2 WAY & CENTRE OFF RED ROCKER
------------------------------------	--	------------------------	--------------------------------------	------------------------------------	--



FINISHES

BRUSHED STAINLESS STEEL STD OPT

LACQUERED BRUSHED STEEL OPT STD

POLISHED BRASS OPT STD

POLISHED CHROME OPT STD

WHITE STD

CHARCOAL STD

BOILER
K4896 BR WHI
K4896 BR BLK

COOKER HOOD
K4896 CH WHI
K4896 CH BLK

CUPBOARD LIGHTING
K4896 CL WHI
K4896 CL BLK

DISHWASHER
K4896 DW WHI
K4896 DW BLK

FAN
K4896 FN WHI
K4896 FN BLK

FREEZER
K4896 FZ WHI
K4896 FZ BLK

FRIDGE
K4896 FG WHI
K4896 FG BLK

HEATER
K4896 HR WHI
K4896 HR BLK

HOB
K4896 HB WHI
K4896 HB BLK

MICROWAVE
K4896 MW WHI
K4896 MW BLK

OVEN
K4896 OV WHI
K4896 OV BLK

TUMBLE DRYER
K4896 TD WHI
K4896 TD BLK

WASHING MACHINE
K4896 WM WHI
K4896 WM BLK

WASTE DISPOSAL
K4896 WD WHI
K4896 WD BLK

BOILER
K4896N BR WHI
K4896N BR BLK

COOKER HOOD
K4896N CH WHI
K4896N CH BLK

CUPBOARD LIGHTING
K4896N CL WHI
K4896N CL BLK

DISHWASHER
K4896N DW WHI
K4896N DW BLK

FAN
K4896N FN WHI
K4896N FN BLK

FREEZER
K4896N FZ WHI
K4896N FZ BLK

FRIDGE
K4896N FG WHI
K4896N FG BLK

HEATER
K4896N HR WHI
K4896N HR BLK

HOB
K4896N HB WHI
K4896N HB BLK

MICROWAVE
K4896N MW WHI
K4896N MW BLK

OVEN
K4896N OV WHI
K4896N OV BLK

TUMBLE DRYER
K4896N TD WHI
K4896N TD BLK

WASHING MACHINE
K4896N WM WHI
K4896N WM BLK

WASTE DISPOSAL
K4896N WD WHI
K4896N WD BLK

K4893 BSS W
K4893 BSS B

K4893 LBS W
K4893 LBS B

K4893 PBR W
K4893 PBR B

K4893 POC W
K4893 POC B

K4893 WHI W

K4893 CHA B

K4893 RED
K4893 RED B

K4893 RED
K4893 RED B

K4893 RED
K4893 RED B

K4893 RED
K4893 RED B

K4893 RED

K4893 RED B

K4899 BSS W
K4899 BSS B

K4899 LBS W
K4899 LBS B

K4899 PBR W
K4899 PBR B

K4899 POC W
K4899 POC B

K4899 WHI W

K4899 CHA B

K4899 RED
K4899 RED B

K4899 RED
K4899 RED B

K4899 RED
K4899 RED B

K4899 RED
K4899 RED B

K4899 RED

K4899 RED B

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.

Additional printed modules available, see pages 168-183.

BS EN 60669-1: 2000

technical hotline +44 (0)1268 563720

decorative | wiring devices

 20 AMP
DP
1 WAY
PUSH MAKE

 20 AMP
SP 2 WAY
RED ROCKER

 20 AMP
SP 2 WAY
WITH NEON
LOCATOR

 20 AMP
DP
1 WAY

 20 AMP
DP
1 WAY
WITH NEON

 20 AMP
DP
1 WAY
WITH WINDOW

 20 AMP
DP
1 WAY
RED ROCKER


K4910 BSS W K4910 BSS B	K4892 RED K4892 RED B	K4892 L WHI K4892 L BLK	K4896 BSS W K4896 BSS B	K4896 N WHI K4896 N BLK	K4896 W WHI K4896 W BLK	K4896 RED K4896 RED B
K4910 LBS W K4910 LBS B	K4892 RED K4892 RED B	K4892 L WHI K4892 L BLK	K4896 LBS W K4896 LBS B	K4896 N WHI K4896 N BLK	K4896 W WHI K4896 W BLK	K4896 RED K4896 RED B
K4910 PBR W K4910 PBR B	K4892 RED K4892 RED B	K4892 L WHI K4892 L BLK	K4896 PBR W K4896 PBR B	K4896 N WHI K4896 N BLK	K4896 W WHI K4896 W BLK	K4896 RED K4896 RED B
K4910 POC W K4910 POC B	K4892 RED K4892 RED B	K4892 L WHI K4892 L BLK	K4896 POC W K4896 POC B	K4896 N WHI K4896 N BLK	K4896 W WHI K4896 W BLK	K4896 RED K4896 RED B
K4910 WHI W	K4892 RED	K4892 L WHI	K4896 WHI W	K4896 N WHI	K4896 W WHI	K4896 RED
	K4892 RED B	K4892 L BLK	K4896 CHA B	K4896 N BLK	K4896 W BLK	K4896 RED B

These switches do NOT have to be derated when used with inductive loads.
Note: Push switches are not designed for fluorescent loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 2000

These switches do NOT have to be derated when used with fluorescent or inductive loads.
BS EN 60669-1: 2000

Switch Modules

20 Amp
DP
1 WAY
PUSH MAKE
RED ROCKER

20 Amp
DP
1 WAY
PUSH BREAK

20 Amp
DP
1 WAY
PUSH BREAK
RED ROCKER

Key Switch Module

20 AMP
SP
KEY SWITCH
2 WAY

20 AMP SP
KEY SWITCH
2 WAY
MARKED
'EMG LTG'

20 AMP
DP
KEY SWITCH
1 WAY



FINISHES

BRUSHED STAINLESS STEEL	<input type="checkbox"/> STD <input type="checkbox"/> OPT	K4910 RED K4910 RED B	K4915 BSS W K4915 BSS B	K4915 RED K4915 RED B	K4898 WHI K4898 BLK	K4898 EL WHI K4898 EL BLK	K4917 WHI K4917 BLK
LACQUERED BRUSHED STEEL	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K4910 RED K4910 RED B		K4915 RED K4915 RED B	K4898 WHI K4898 BLK	K4898 EL WHI K4898 EL BLK	K4917 WHI K4917 BLK
POLISHED BRASS	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K4910 RED K4910 RED B		K4915 RED K4915 RED B	K4898 WHI K4898 BLK	K4898 EL WHI K4898 EL BLK	K4917 WHI K4917 BLK
POLISHED CHROME	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K4910 RED K4910 RED B		K4915 RED K4915 RED B	K4898 WHI K4898 BLK	K4898 EL WHI K4898 EL BLK	K4917 WHI K4917 BLK
WHITE	<input type="checkbox"/> STD	K4910 RED	K4915 WHI W	K4915 RED	K4898 WHI	K4898 EL WHI	K4917 WHI
CHARCOAL	<input type="checkbox"/> STD	K4910 RED B	K4915 CHA B	K4915 RED B	K4898 BLK	K4898 EL BLK	K4917 BLK

These switches do NOT have to be derated when used with inductive loads.

Note: Push switches are not designed for fluorescent loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with inductive loads.

Note: Push switches are not designed for fluorescent loads.

BS EN 60669-1: 2000

These switches do NOT have to be derated when used with inductive loads.

Note: Push switches are not designed for fluorescent loads.

BS EN 60669-1: 2000

BS EN 60669-1: 2000
Key (3405 NIP) is supplied.

BS EN 60669-1: 2000
Key (3405 NIP) is supplied.

BS EN 60669-1: 2000
Key (3405 NIP) is supplied.

technical hotline +44 (0)1268 563720

decorative | wiring devices

Indicator Modules

	20 AMP SP KEY SWITCH							
20 AMP INTERMEDIATE KEY SWITCH	2 WAY BIASED 1 WAY	200-250 VOLT RED	200-250 VOLT GREEN	200-250 VOLT AMBER	21-36 VOLT RED	21-36 VOLT GREEN	21-36 VOLT AMBER	

K4894 WHI K4894 BLK	K4918 WHI K4918 BLK	K4889 RED K4889 RED B	K4889 GRN K4889 GRN B	K4889 AMB K4889 AMB B	K4836 RED K4836 RED B	K4836 GRN K4836 GRN B	K4836 AMB K4836 AMB B
K4894 WHI K4894 BLK	K4918 WHI K4918 BLK	K4889 RED K4889 RED B	K4889 GRN K4889 GRN B	K4889 AMB K4889 AMB B	K4836 RED K4836 RED B	K4836 GRN K4836 GRN B	K4836 AMB K4836 AMB B
K4894 WHI K4894 BLK	K4918 WHI K4918 BLK	K4889 RED K4889 RED B	K4889 GRN K4889 GRN B	K4889 AMB K4889 AMB B	K4836 RED K4836 RED B	K4836 GRN K4836 GRN B	K4836 AMB K4836 AMB B
K4894 WHI K4894 BLK	K4918 WHI K4918 BLK	K4889 RED K4915 RED B	K4889 GRN K4915 GRN B	K4889 AMB K4915 AMB B	K4836 RED K4836 RED B	K4836 GRN K4836 GRN B	K4836 AMB K4836 AMB B
K4894 WHI	K4918 WHI	K4889 RED	K4889 GRN	K4889 AMB	K4836 RED	K4836 GRN	K4836 AMB
K4894 BLK	K4918 BLK	K4889 RED B	K4889 GRN B	K4889 AMB B	K4836 RED B	K4836 GRN B	K4836 AMB B

 BS EN 60669-1: 2000
Key (3405 ZIC)
is supplied.

 BS EN 60669-1: 2000
Key (3405 ZIC)
is supplied.

BS 5733: 1995

BS 5733: 1995

BS 5733: 1995

BS 5733: 1995

BS 5733: 1995

BS 5733: 1995

Dimmer Switch Modules

1 GANG 40W/ VA-220W/180VA, 230VA.C, 50HZ TWO WAY 1 MODULE	1 GANG 60W/ VA-400W/320VA, 230VA.C, 50HZ TWO WAY 2 MODULE	1 GANG 1-10V FLUORESCENT
---	---	--------------------------------

Accessory Modules

TV CO-AXIAL OUTLET NON-ISOLATED	TV CO-AXIAL OUTLET ISOLATED	16 AMP CORD OUTLET
---------------------------------------	-----------------------------------	-----------------------



FINISHES

BRUSHED STAINLESS STEEL	STD	K4501 BSS W LV	K4500 BSS W LV	K4499 BSS W	K4520 WHI	K4521 WHI	K4886 WHI
	OPT	K4501 BSS B LV	K4500 BSS B LV	K4499 BSS B	K4520 BLK	K4521 BLK	K4886 BLK
LACQUERED BRUSHED STEEL	OPT	K4501 LBS W LV	K4500 LBS W LV		K4520 WHI	K4521 WHI	K4886 WHI
	STD	K4501 LBS B LV	K4500 LBS B LV		K4520 BLK	K4521 BLK	K4886 BLK
POLISHED BRASS	OPT	K4501 PBR W LV	K4500 PBR W LV		K4520 WHI	K4521 WHI	K4886 WHI
	STD	K4501 PBR B LV	K4500 PBR B LV		K4520 BLK	K4521 BLK	K4886 BLK
POLISHED CHROME	OPT	K4501 POC W LV	K4500 POC W LV		K4520 WHI	K4521 WHI	K4886 WHI
	STD	K4501 POC B LV	K4500 POC B LV		K4520 BLK	K4521 BLK	K4886 BLK
WHITE	STD	K4501 WHI W LV	K4500 WHI W LV	K4499 WHI W	K4520 WHI	K4521 WHI	K4886 WHI
CHARCOAL	STD	K4501 CHA B LV*	K4500 CHA B LV*	K4499 CHA B	K4520 BLK	K4521 BLK	K4886 BLK

These dimmers incorporate the latest in micro-controller based circuitry to provide electronic soft-start and overload protection. They are radio frequency interference suppressed to BS EN 55015.

Suitable for use with good quality electronic or wire wound transformers. Can also be used with good quality mains voltage halogen lamps incorporating GU10 bases. Please check with lamp manufacturer to determine suitability.

Matching metal decorative caps are standard on all Aspect Grid Dimmers (except WHI).

K4500 is only suitable for use in 2, 4 and 8 module grids.

They are not suitable for fluorescent lamps.

Note: Refer to technical section for derating factors when more than one unit is used in any one box.

Conforms to the latest standard BS EN 60669-2-1.

For direct connection to TV or FM aerial co-axial download.

Not to be used in same enclosure as mains exceeding 50V.

For direct connection to TV or FM aerial co-axial download.

Not to be used in same enclosure as mains exceeding 50V.

Provides safety isolation rated at 2KV between aerial lead and socket.

Complete with 3 pairs of terminals. The supply terminals are suitable for up to 2 x 2.5mm² or 1 x 4mm² solid conductors. The load terminals are suitable for one 1.5mm² flexible cord.

A cord grip is also fitted. BS 5733: 1995

LEAD TIMES

Please contact our Customer Services Department on: 01268 563000

technical hotline +44 (0)1268 563720

decorative | wiring devices

13 AMP
FUSE UNIT
WITH
TAMPERPROOF
SCREW

13 AMP
FUSE UNIT

BLANK INSERT

BUZZER UNIT
230 VOLT

K4890 WHI K4890 BLK	K4890KO WHI K4890KO BLK	K4880 BSS W K4880 BSS B	K4000 WHI K4000 BLK
K4890 WHI K4890 BLK	K4890KO WHI K4890KO BLK	K4880 LBS W K4880 LBS B	K4000 WHI K4000 BLK
K4890 WHI K4890 BLK	K4890KO WHI K4890KO BLK	K4880 PBR W K4880PBR B	K4000 WHI K4000 BLK
K4890 WHI K4890 BLK	K4890KO WHI K4890KO BLK	K4880 POC W K4880 POC B	K4000 WHI K4000 BLK
K4890 WHI	K4890KO WHI	K4880 WHI W	K4000 WHI
K4890 BLK	K4890KO BLK	K4880 CHA B*	K4000 BLK



Fuse carrier comes with 13amp cartridge fuse link to BS 1362.
BS 5733: 1995

Fuse carrier comes with 13amp cartridge fuse link to BS 1362.
BS 5733: 1995

Matching metal decorative caps are standard on all Aspect Grid Blank Inserts (except WHI).
BS 5733: 1995

200-250V
BS 5733: 1995

Power Modules

16 AMP 1 MODULE UNIVERSAL SOCKET (NON UK)	GERMAN 2P+E 16 AMP 250V SHUTTERED EURO* 2 MODULE (NON UK)	UK 1 GANG 5 AMP 250V SHUTTERED EURO* 2 MODULE	UK 1 GANG 5 AMP 250V SHUTTERED EURO* 2 MODULE	FRENCH/BELGIAN 2P+E 16AMP 250V SHUTTERED EURO* 2 MODULE (NON UK)
---	---	---	---	--



FINISHES

FINISHES						
BRUSHED STAINLESS STEEL	STD	K4901 WHI	K5831 WHI	K5830 WHI	K5833 WHI	K5834 WHI
	OPT	K4901 BLK	K5831 BLK	K5830 BLK	K5833 BLK	K5834 BLK
LACQUERED BRUSHED STEEL	OPT	K4901 WHI	K5831 WHI	K5830 WHI	K5833 WHI	K5834 WHI
	STD	K4901 BLK	K5831 BLK	K5830 BLK	K5833 BLK	K5834 BLK
POLISHED BRASS	OPT	K4901 WHI	K5831 WHI	K5830 WHI	K5833 WHI	K5834 WHI
	STD	K4901 BLK	K5831 BLK	K5830 BLK	K5833 BLK	K5834 BLK
POLISHED CHROME	OPT	K4901 WHI	K5831 WHI	K5830 WHI	K5833 WHI	K5834 WHI
	STD	K4901 BLK	K5831 BLK	K5830 BLK	K5833 BLK	K5834 BLK
WHITE	STD	K4901 WHI	K5831 WHI	K5830 WHI	K5833 WHI	K5834 WHI
CHARCOAL	STD	K4901 BLK	K5831 BLK	K5830 BLK	K5833 BLK	K5834 BLK

MOUNTING BOX:
35mm minimum
46mm for extra
wiring space.

The Universal Socket does not incorporate an earth contact. Appliances needing earth connection (class 1 equipment) must NOT be used with this socket.

The socket is intended for use with BS, USA and CEE standard plugs.

BS 5733: 1995

MOUNTING BOX:
46mm
DIMENSIONS:
50 x 50mm

IEC 60884-1: 2006

MOUNTING BOX:
35mm minimum
46mm for extra
wiring space.

DIMENSIONS:
50 x 50mm

BS 1363 Part 2: 1995

MOUNTING BOX:
35mm minimum
46mm for extra
wiring space.

DIMENSIONS:
50 x 50mm

BS 546: 1950

MOUNTING BOX:
46mm

DIMENSIONS:
50 x 50mm

NFC61-341

LEAD TIMES

Please contact our Customer Services Department on: 01268 563000

Mains operated products and extra low voltage modules must not be installed within the same frontplate aperture. Refer to BS 7671: 2008 for details.

* Euro frontplates can be found on page 92

technical hotline +44 (0)1268 563720

decorative | wiring devices

Intelligent Dimmers (CE marked)

2 WAY SINGLE 230V a.c. 50Hz 60W/VA MIN- 500W/400VA MAX.	2 WAY SINGLE 230V a.c. 50Hz 40W/VA MIN. 300W/240VA MAX.	2 WAY DOUBLE 230V a.c. 50Hz 40W/VA MIN. 300W/240VA MAX. FOR EACH DIMMER
---	---	--

Dimmers (NON UK)

220V a.c. 50Hz 60-500W SINGLE	220V a.c. 50Hz 100-1000W SINGLE	220V a.c. 60Hz 100-1000W SINGLE
-------------------------------------	---------------------------------------	---------------------------------------

K24301 BSS	K24521 BSS	K24522 BSS	K24541 BSS	K24561 BSS	K24661 BSS
K24301 LBS		K24522 LBS			
K24301 PBR	K24521 PBR	K24522 PBR	K24541 PBR	K24561 PBR	K24661 PBR
K24301 POC	K24521 POC	K24522 POC	K24541 POC	K24561 POC	K24661 POC
K24301 WHI	K24521 WHI	K24522 WHI	K24541 WHI	K24561 WHI	K24661 WHI
K24301 CHA	K24521 CHA	K24522 CHA	K24541 CHA	K24561 CHA	K24661 CHA

 MOUNTING BOXES:
FLUSH 866 ZIC –
35mm deep min

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

These dimmers employ the latest micro-controller based circuitry to provide electronic soft-start and overload protection. They are suitable for use with good quality electronic or wire-wound transformers. Can also be used with good quality halogen lamps incorporating GU10 bases. Please check with lamp manufacturer to determine suitability.

NOT SUITABLE FOR FLUORESCENT LOADS.

Conform to latest standards BS EN 60669-2-1.

All intelligent dimmers have a combined push-on/push-off switch and rotary dimmer control, and are suitable for one or two-way switching. Only one dimmer can be used in a two way switching circuit.

They are radio frequency interference suppressed to BS EN 55015.

 MOUNTING BOXES:
FLUSH 866 ZIC –
35mm deep min

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

 MOUNTING BOXES:
FLUSH 866 ZIC –
35mm deep min

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

 MOUNTING BOXES:
FLUSH 866 ZIC –
35mm deep min.

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

 Suitable for tungsten
GLS lamps only, with
internal fuses.

 NOT SUITABLE FOR
FLUORESCENT LOADS.

 MOUNTING BOXES:
FLUSH 866 ZIC –
35mm deep min.

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm

 Suitable for tungsten
GLS lamps only, with
internal fuses.

 NOT SUITABLE FOR
FLUORESCENT LOADS.

 MOUNTING BOXES:
FLUSH 866 ZIC –
35mm deep min.

 DIMENSIONS:
86 x 86mm

 FIXING CENTRES:
60.3mm


 Suitable for tungsten
GLS lamps only, with
internal fuses.

 NOT SUITABLE FOR
FLUORESCENT LOADS.

Datacom Frontplates

SUPPLIED WITH MOUNTING FRAME

EURO 1 MODULE 25 X 50mm	EURO 2 MODULE 50 X 50mm	EURO 4 MODULE 100 X 50mm	LJU6C 1 GANG 1 MODULE	LJU6C 1 GANG 2 MODULE	LJU6C 2 GANG 4 MODULE
-------------------------------	-------------------------------	--------------------------------	-----------------------------	-----------------------------	-----------------------------



FINISHES

BRUSHED STAINLESS STEEL	<input type="checkbox"/> STD <input type="checkbox"/> OPT	K24181 BSS	K24182 BSS	K24184 BSS	K24171 BSS	K24172 BSS	K24174 BSS
LACQUERED BRUSHED STEEL	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K24181 LBS	K24182 LBS	K24184 LBS		K24172 LBS	
POLISHED BRASS	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K24181 PBR	K24182 PBR	K24184 PBR	K24171 PBR	K24172 PBR	K24174 PBR
POLISHED CHROME	<input type="checkbox"/> OPT <input type="checkbox"/> STD	K24181 POC	K24182 POC	K24184 POC	K24171 POC	K24172 POC	K24174 POC
WHITE	<input type="checkbox"/> STD	K24181 WHI	K24182 WHI	K24184 WHI	K24171 WHI	K24172 WHI	K24174 WHI
CHARCOAL	<input type="checkbox"/> STD	K24181 CHA	K24182 CHA	K24184 CHA	K24171 CHA	K24172 CHA	K24174 CHA

MOUNTING BOXES:
Suitable for flush boxes to BS 4662: 2006 and surface boxes to BS 5733: 1995
Refer to appropriate module for minimum box depth.

FIXING CENTRES:
60.3mm

BS 5733: 1995 where applicable

MOUNTING BOXES:
Suitable for flush boxes to BS 4662: 2006 and surface boxes to BS 5733: 1995
Refer to appropriate module for minimum box depth.

FIXING CENTRES:
60.3mm

BS 5733: 1995 where applicable

MOUNTING BOXES:
Suitable for flush boxes to BS 4662: 2006 and surface boxes to BS 5733: 1995
Refer to appropriate module for minimum box depth.

FIXING CENTRES:
120.6mm

BS 5733: 1995 where applicable

MOUNTING BOXES:
Suitable for flush boxes to BS 4662: 2006 and surface boxes to BS 5733: 1995
Refer to appropriate module for minimum box depth.

FIXING CENTRES:
60.3mm

BS 5733: 1995 where applicable

MOUNTING BOXES:
Suitable for flush boxes to BS 4662: 2006 and surface boxes to BS 5733: 1995
Refer to appropriate module for minimum box depth.

FIXING CENTRES:
60.3mm

BS 5733: 1995 where applicable

MOUNTING BOXES:
suitable for flush boxes to BS 4662: 2006 and surface boxes to BS 5733: 1995
Refer to appropriate module for minimum box depth.

FIXING CENTRES:
120.6mm

BS 5733: 1995 where applicable

technical hotline +44 (0)1268 563720

decorative | wiring devices

Datacom Modules

RJ45 CAT 6 EURO 1 MODULE	RJ45 CAT 6 LB SCREENED EURO 1 MODULE	RJ45 ANGLED CAT 6 EURO 1 MODULE	RJ45 CAT 5E (UTP) EURO 1 MODULE	RJ45 ANGLED CAT 5E (UTP) EURO 1 MODULE	BNC 50 Ω EURO 1 MODULE
-----------------------------------	--	---	---	---	---------------------------------

K5846 WHI K5846 BLK	K5846s WHI K5846s BLK	K5864 WHI	K5845 WHI K5845 BLK	K5844 WHI	K5801 WHI
K5846 WHI K5846 BLK	K5846s WHI K5846s BLK	K5864 WHI	K5845 WHI K5845 BLK	K5844 WHI	K5801 WHI
K5846 WHI K5846 BLK	K5846s WHI K5846s BLK	K5864 WHI	K5845 WHI K5845 BLK	K5844 WHI	K5801 WHI
K5846 WHI	K5846s WHI	K5864 WHI	K5845 WHI	K5844 WHI	K5801 WHI
K5846 BLK	K5846s BLK	K5864 WHI	K5845 BLK	K5844 WHI	K5801 WHI

RJ45 Modules

Enhanced Cat 6 performance.

Suitable for both 568A and 568B wiring schemes.

 MOUNTING BOXES:
35mm minimum

 TIA/EIA TSB40A: Cat 6
TIA/EIA 568-A: Cat 6
ISO/IEC11801: Cat 6

Enhanced Cat 5 performance.

Suitable for both 568A and 568B wiring schemes.

 MOUNTING BOXES:
25mm minimum

 TIA/EIA TSB40A: Cat 5e
TIA/EIA 568-A: Cat 5e
ISO/IEC11801: Cat 5e

50 Ohm crimp connector suitable for use with RG58, URM43, URM76 and Belden 9907 type co-axial cables.

 MOUNTING BOXES:
Min. box depth
25mm

Datacom Modules

RJ45
CAT 6
LJU6C
1 MODULE

RJ45
CAT 6
SCREENED
LJU6C
1 MODULE

TV Coaxial Outlets suitable for Analogue and Digital TV

SINGLE
IEC MALE
EURO
1 MODULE

SINGLE
IEC FEMALE
EURO
1 MODULE

F-TYPE
SATELLITE
EURO
1 MODULE

FINISHES					
BRUSHED STAINLESS STEEL	<input type="checkbox"/> STD <input type="checkbox"/> OPT K5746 WHI K5746 BLK	K5746s WHI K5746s BLK	K5850 WHI K5850 BLK	K5851 WHI K5851 BLK	K5855 WHI K5855 BLK
LACQUERED BRUSHED STEEL	<input type="checkbox"/> OPT <input type="checkbox"/> STD K5746 WHI K5746 BLK	K5746s WHI K5746s BLK	K5850 WHI K5850 BLK	K5851 WHI K5851 BLK	K5855 WHI K5855 BLK
POLISHED BRASS	<input type="checkbox"/> OPT <input type="checkbox"/> STD K5746 WHI K5746 BLK	K5746s WHI K5746s BLK	K5850 WHI K5850 BLK	K5851 WHI K5851 BLK	K5855 WHI K5855 BLK
POLISHED CHROME	<input type="checkbox"/> OPT <input type="checkbox"/> STD K5746 WHI K5746 BLK	K5746s WHI K5746s BLK	K5850 WHI K5850 BLK	K5851 WHI K5851 BLK	K5855 WHI K5855 BLK
WHITE	<input type="checkbox"/> STD K5746 WHI	K5746s WHI	K5850 WHI	K5851 WHI	K5855 WHI
CHARCOAL	<input type="checkbox"/> STD K5746 BLK	K5746s BLK	K5850 BLK	K5851 BLK	K5855 BLK

Fully Screened non isolated TV outlets containing a combination of single, TV/FM Diplexer and TV/FM/SAT Triplexer for use within digital TV systems and interactive TV services. Single outlets for connection to a single TV, FM or Satellite co-axial aerial lead.

TV/FM diplexer units for connection to a single co-axial aerial lead with combined TV and FM signals.

TV/FM/SAT triplexer units for connection to a single co-axial aerial lead with combined TV, FM and Satellite signals.

Enhanced Cat 6 performance.
Suitable for both 568A and 568B wiring schemes.
MOUNTING BOXES:
35mm minimum
TIA/EIA TSB40A: Cat 6
TIA/EIA 568-A: Cat 6
ISO/IEC11801: Cat 6

MOUNTING BOXES:
Min box depth 32mm
DIMENSIONS:
1 Module 25 x 50mm
2 Module 50 x 50mm
BS 3041: 1997
IEC 169-2: 1965
BS EN 50083 &
BS 5733: 1995
where applicable

PERFORMANCE:
SINGLE OUTLETS
TV/FM IEC MALE OR
FEMALE
DC-950MHz
SAT F-TYPE
DC-1.75GHz

technical hotline +44 (0)1268 563720

decorative | wiring devices

TV/FM
DIPLEXER
EURO
2 MODULE

TV/FM/SAT
TRIPLEXER
EURO
2 MODULE

TWIN OUTLET
TV-FM/DAB
DIPLEXER
TWO MODULE
50 X 50mm

TRIPLE OUTLET
TV-FM/DAB-
SAT TRIPLEXER
TWO MODULE
50 X 50mm

QUAD OUTLET
TV-FM/DAB-
2XSAT
TWO MODULE
50 X 50mm

Telecom Modules

MASTER
BT
EURO
1 MODULE

K5852 WHI K5852 BLK	K5853 WHI K5853 BLK	K5852 DAB WHI K5852 DAB BLK	K5853 DAB WHI K5853 DAB BLK	K5854 DAB WHI K5854 DAB BLK	K5820 WHI K5820 BLK
K5852 WHI K5852 BLK	K5853 WHI K5853 BLK	K5852 DAB WHI K5852 DAB BLK	K5853 DAB WHI K5853 DAB BLK	K5854 DAB WHI K5854 DAB BLK	K5820 WHI K5820 BLK
K5852 WHI K5852 BLK	K5853 WHI K5853 BLK	K5852 DAB WHI K5852 DAB BLK	K5853 DAB WHI K5853 DAB BLK	K5854 DAB WHI K5854 DAB BLK	K5820 WHI K5820 BLK
K5852 WHI	K5853 WHI	K5852 DAB WHI	K5853 DAB WHI	K5854 DAB WHI	K5820 WHI
K5852 BLK	K5853 BLK	K5852 DAB BLK	K5853 DAB BLK	K5854 DAB BLK	K5820 BLK

TV/FM diplexer units for connection to a single co-axial aerial lead with combined TV and FM signals.

TV/FM/SAT triplexer units for connection to a single co-axial aerial lead with combined TV, FM and Satellite signals.

DIPLEXER AND TRIPLEXER PRODUCTS

TV/FM/SAT PRODUCTS

OUTLET
TV
FM
SAT

DIPLEXER
DC-68.5MHz,
174-862MHz
87.5-108MHz
N/A

TRIPLEXER
DC-68.5MHz,
174-862MHz
87.5-108MHz
DC-200kHz,
950-2400MHz

TWIN OUTLET

TV-FM/DAB
Diplexer

Two module
50 x 50mm

TRIPLE OUTLET

TV-FM/DAB – SAT
Triplexer

Two module
50 x 50mm

QUAD OUTLET

TV-FM/DAB –
2 x SAT

Two module
50 x 50mm

MOUNTING BOXES:

Min. box depth
25mm
BS 6312 Pt 2

TV/FM/DAB/SAT PRODUCTS

FOR DIGITAL RADIO

OUTLET
TV
FM/DAB
SAT OR
SAT1
SAT2

DIPLEXER
470-862MHz
87.5-230MHz

TRIPLEXER / QUAD OUTLET
470-862MHz
87.5-230MHz
950-2400MHz
DC-2300MHz

These products are fully compatible with Labgear TV distribution systems and are approved for use in "Sky Homes" and "Homes On" specifications

Mains operated products and extra low voltage modules must not be installed within the same frontplate aperture. Refer to BS 7671: 2008 for details.

Datacom Modules

RJ11/RJ12
EURO
1 MODULE

EURO BLANK
2 MODULE
(50X50mm)

EURO BLANK
1 MODULE
(25X50mm)







EURO BLANK
1/2 MODULE
(12.5X50mm)

Blank Plates

SUPPLIED WITH MOUNTING
FRAME

1 GANG

2 GANG

						
FINISHES						
BRUSHED STAINLESS STEEL	[STD] K5887 WHI [OPT] K5887 BLK	K180 WHI K188 BLK x 2	K188 WHI K188 BLK	K186 WHI K186 BLK	K24330 BSS	K24329 BSS
LACQUERED BRUSHED STEEL	[OPT] K5887 WHI [STD] K5887 BLK	K180 WHI K188 BLK x 2	K188 WHI K188 BLK	K186 WHI K186 BLK	K24330 LBS	K24329 LBS
POLISHED BRASS	[OPT] K5887 WHI [STD] K5887 BLK	K180 WHI K188 BLK x 2	K188 WHI K188 BLK	K186 WHI K186 BLK	K24330 PBR	K24329 PBR
POLISHED CHROME	[OPT] K5887 WHI [STD] K5887 BLK	K180 WHI K188 BLK x 2	K188 WHI K188 BLK	K186 WHI K186 BLK	K24330 POC	K24329 POC
WHITE	[STD] K5887 WHI	K180 WHI	K188 WHI	K186 WHI	K24330 WHI	K24329 WHI
CHARCOAL	[STD] K5887 BLK	K188 BLK x 2	K188 BLK	K186 BLK	K24330 CHA	K24329 CHA

Suitable for both RJ11 and RJ12 jacks.

RJ11: 4 wire
RJ12: 6 wire

MOUNTING BOXES:
Min. box depth
25mm
FCC68

MOUNTING BOXES:
Min. box depth 16mm

BS 5733: 1995
where applicable

MOUNTING BOXES:
Min. box depth 16mm

BS 5733: 1995
where applicable

MOUNTING BOXES:
Min. box depth 16mm

BS 5733: 1995
where applicable

MOUNTING BOXES:
FLUSH 35mm: 866 ZIC
FLUSH 46mm: 877 ZIC
(for extra wiring space)

DIMENSIONS:
86 x 86mm
FIXING CENTRES:
60.3mm
BS 5733: 1995

MOUNTING BOXES:
FLUSH 35mm: 886 ZIC
FLUSH 47mm: 878 ZIC
(for extra wiring space)

DIMENSIONS:
86 x 146mm
FIXING CENTRES:
120.6mm
BS 5733: 1995

LEAD TIMES

Please contact our Customer Services Department on: 01268 563000