

HDB6IS Switch Disconnecter

Standard: IEC 60947-3




Function


- HDB6IS switch disconnecters combine the following functions:
- Making and breaking normal load circuits
 - Isolation

Order Information




Type	Rating (A)	Width (in mod.of 9mm)	Reference
1P 	20	2	HDB6IS120
	32	2	HDB6IS132
	63	2	HDB6IS163
	100	2	HDB6IS1100
	125	2	HDB6IS1125




2P 	20	4	HDB6IS220
	32	4	HDB6IS232
	63	4	HDB6IS263
	100	4	HDB6IS2100
	125	4	HDB6IS2125



3P 	20	6	HDB6IS320
	32	6	HDB6IS332
	63	6	HDB6IS363
	100	6	HDB6IS3100
	125	6	HDB6IS3125



4P 	20	8	HDB6IS420
	32	8	HDB6IS432
	63	8	HDB6IS463
	100	8	HDB6IS4100
	125	8	HDB6IS4125

Final Distribution

SUPERMOON

Powering modern work and life

Order at 訂貨熱線 :

香港批發 / 分銷 T (852) 2781 2855

澳門批發 / 分銷 T (853) 2822 2751

工程 / 商業項目 T (852) 2691 9166

E enquiry@supermoon.hk

www.supermoon.hk

HDB6IS Switch Disconnecter

Standard: IEC 60947-3



Technical Data

Switch Disconnecter	HDB6IS Switch Disconnecter			
Electrical Features	Standard	IEC60947-3		
	Certification	CB,CE,SEMKO		
	Poles	1-4P		
	Rated Current In	20, 32, 63, 100,125A		
	Rated Voltage Ue	230/400V AC		
	Insulation Voltage Ui	500V		
	Short-time Withstand Capacity for 1s	12Ie		
Mechanical Features	Electrical Durability	1500 times		
	Mechanical Durability	8500 times		
	Protection Degree	2		
	Ambient Temperature	- 5°C ~ +40°C		
	Tropicalization	treatment 2		
Connection	Up to 50mm ² cables			
Installation	Rate current(A)	Screw	Rated Torque (Nm)	Limiting Torque (Nm)
	20-125	M7	4	5.5
Mounting	35mm Din-rail			

Final Distribution

Overall Dimensions

Unit: mm

