











- Complies with BS EN 60669-1 IEC 60669-1 CB certificate
- 'AX' rated - No need to derate for fluorescent loads
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
3 x 1.5 mm²
2 X 2.5 mm²
- Two way switches can be wired either 1 way or 2 way
- Terminal markings denote:
L1 = one way
L2 = two way
C = common
- Material: Polycarbonate




Description		Pack qty.	Cat. Ref.
	Single pole switches 10AX 1 gang 1 way, large dolly	10	WXEL111
	1 gang 2 way, large dolly	10	WXEL112
	2 gang 1 way, large dolly	10	WXEL121
	2 gang 2 way, large dolly	10	WXEL122
	3 gang 1 way, large dolly	10	WXEL131
	3 gang 2 way, large dolly	10	WXEL132
	1 gang intermediate large dolly	10	WXEL101

stylea
bell switches

- Complies with BS EN 60669-1 IEC 60669-1 CB certificate
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
3 x 1.5 mm²
2 X 2.5 mm²
- Material: Polycarbonate







Description		Pack qty.	Cat. Ref.
	Single pole bell switches 10A Marked "BELL" large dolly	10	WXEL11B
	Marked "PRESS" large dolly	10	WXEL11P
	2 gang marked "PRESS" large dolly	10	WXEL12P



- Complies with BS EN 60669-2-1 IEC 60669-2-1
 - Supplied with M3.5 x 25 mm long fixing screws
 - Capacity of each terminal: 3 x 1.5 mm²
 - Material: Polycarbonate
- For dimmers**
- Frequency 50/ 60Hz
 - Rating 500W max
 - For incandescent lamps only
 - Max 150W for halogen lamps

Description		Pack qty.	Cat. Ref.
	Dimmer switches 500W 2 way switched single	5	WXED1R500
	500W 2 way switched twin	5	WXED2R500
	Fan controller 400W 2 way switched	5	WXEF1R400

stylea
double pole control switches



- Complies with BS EN 60669-1 IEC 60669-1 CB certificate
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
L, N: 2 x 4 mm²
E: 2 x 4 mm²
- Material: Polycarbonate

Description		Pack qty.	Cat. Ref.
	Double pole control switches 20AX 1 gang, large dolly	10	WXEL2D1
	1 gang, large dolly with neon	10	WXEL2D1N
	2 gang, large dolly	10	WXEL2D2
	2 gang, large dolly with neon	10	WXEL2D2N
	1 gang 2 way, large dolly	10	WXEL2D12
	1 gang 2 way, large dolly with neon	10	WXEL2D12N

		Description	Pack qty.	Cat. Ref.																														
 WXEL2D1NWH	 WXEL2D1NAX	Double pole control switch 20AX with special marking 1 gang, large dolly with neon marked "WATER HEATER"	10	WXEL2D1NWH																														
		1 gang, large dolly with neon marked "20AX"	10	WXEL2D1NAX																														
		<table border="1"> <thead> <tr> <th>Special marks</th> <th>Abbreviation</th> <th>Special marks</th> <th>Abbreviation</th> <th>Special marks</th> <th>Abbreviation</th> </tr> </thead> <tbody> <tr> <td>"AIR CONDITIONER"</td> <td>AC</td> <td>"DRYER"</td> <td>DR</td> <td>"OVEN"</td> <td>OV</td> </tr> <tr> <td>"COOKER HOB"</td> <td>CB</td> <td>"DISH WASHER"</td> <td>DW</td> <td>"WATER HEATER"</td> <td>WH</td> </tr> <tr> <td>"COOKER HOOD"</td> <td>CH</td> <td>"FRIDGE"</td> <td>FR</td> <td>"WASHING MACHINE"</td> <td>WM</td> </tr> <tr> <td>"COMPUTER POWER"</td> <td>CP</td> <td>"20AX"</td> <td>AX</td> <td></td> <td></td> </tr> </tbody> </table> (Surcharge applies)	Special marks	Abbreviation	Special marks	Abbreviation	Special marks	Abbreviation	"AIR CONDITIONER"	AC	"DRYER"	DR	"OVEN"	OV	"COOKER HOB"	CB	"DISH WASHER"	DW	"WATER HEATER"	WH	"COOKER HOOD"	CH	"FRIDGE"	FR	"WASHING MACHINE"	WM	"COMPUTER POWER"	CP	"20AX"	AX				
Special marks	Abbreviation	Special marks	Abbreviation	Special marks	Abbreviation																													
"AIR CONDITIONER"	AC	"DRYER"	DR	"OVEN"	OV																													
"COOKER HOB"	CB	"DISH WASHER"	DW	"WATER HEATER"	WH																													
"COOKER HOOD"	CH	"FRIDGE"	FR	"WASHING MACHINE"	WM																													
"COMPUTER POWER"	CP	"20AX"	AX																															


stylea 32A and 45A double pole control switches

- Complies with BS EN 60669-1 IEC 60669-1, CB certificate
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
L, N: 1 X 16.0 mm²
E: 2 X 16.0 mm²
- Material: polycarbonate

		Description	Pack qty.	Cat. Ref.
 WXER32D1 WXER45D1	 WXER45D2	Double pole control switches 32A with neon	10	WXER32D1
		45A with neon	10	WXER45D1
		45A with neon (size 2)	5	WXER45D2



















stylea cooker control unit

- Complies with BS 4177
- Combined switch / sockets have double pole 45A main switch & 13A switched socket outlet
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
L, N: 1 x 16 mm²
E: 1 x 10 mm²
- Marking on cooker control units: ON, OFF and circuit identification cooker and socket
- Material: Polycarbonate

		Description	Pack qty.	Cat. Ref.
 WXER45CCU		Double pole cooker control unit 45A Cooker control unit (size 2)	5	WXER45CCU

• Supplied with M3.5 x 25 mm long fixing screws

• Material: Polycarbonate

		Description	Pack qty.	Cat. Ref.
Communication and data				
		Telephone outlet (BS style master)	10	WXET1M
WXET1M	WXET1S	Telephone outlet (BS style slave)	10	WXET1S
		FM co-axial outlet	10	WXETFM75
WXETFM75	WXETV75	TV co-axial outlet	10	WXETV75
		TV + FM splitter isolator SCV outlet (size 2)	10	WXETVFM2
		TV + FM connector	10	WXETVFM
WXETVFM2		TV + FM outlet with splitter	10	WXETVFMWS
		RJ45 data outlet (1 mod) Cat 5e	10	WXET1RJ5
WXET1RJ5	WXET2RJ5	RJ45 data outlet (2 mod) Cat 5e	10	WXET2RJ5
		RJ45 data outlet (1 mod) Cat 6	10	WXET1RJ6
WXET1RJ6	WXET2RJ6	RJ45 data outlet (2 mod) Cat 6	10	WXET2RJ6
		RJ11 telephone + RJ45 data outlet Cat 5e	10	WXETD
WXETD		RJ11 telephone outlet (1 mod)	10	WXET1RJ
	WXET1RJ	RJ11 telephone outlet (2 mod)	10	WXET2RJ
		RG6 cable TV outlet	10	WXETV75F
WXET2RJ	WXETV75F	Branching terminal 5-pair tel. terminal	10	WXETBT5
		TV + RG6 connector without splitter	10	WXETV75R
WXET2A		2A telephone socket with shutter	10	WXET2A
	WXETV75R	TV + FM outlet (master)	10	WXETV75R
		TV + FM outlet (slave)	10	WXETV75R
WXET2A	WXETV75R WXETV75S			

stylea 5A socket outlets



- Complies with BS 546 SS 472

- Supplied with M3.5 x 25 mm long fixing screws

- Capacity of each terminal:
L, N: 3 X 2.5 mm²
E: 4 X 1.5 mm²

- Integral rocker design of switched sockets provides clear red 'on' indication

- Material: Polycarbonate

		Description	Pack qty.	Cat. Ref.
		Socket outlet 5A round pin unswitched	10	WXES105
		5A round pin switched	10	WXES105S
WXES105	WXES105S			

stylea 10A socket outlet




- Complies with IEC 60884-2-3

- Supplied with M3.5 x 25 mm long fixing screws







- Integral rocker design of switched sockets provides clear red 'on' indication

- Material: Polycarbonate

- Capacity of each terminal:
L, N: 2 X 4.0 mm²
E: 3 X 2.5 mm²

		Description	Pack qty.	Cat. Ref.
		Socket outlets 10A 2 pin unswitched universal	10	WXES10U
		10A 2 pin switched universal	10	WXES10US
		10A 2 pin unswitched twin universal	10	WXES10U2
WXES10U	WXES10US			
WXES10U2				

- Complies with BS 1363-2 SS 145-2
- All terminal screws are facing upward for ease of installation
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
L, N: 2 x 4.0 mm²
E: 3 x 2.5 mm²
- Integral rocker design of switched sockets provides clear red 'on' indication
- Tough plastic back for durability
- Material: Polycarbonate

		Description	Pack qty.	Cat. Ref.
		Socket outlets 13A single unswitched	10	WXES113
		13A twin unswitched (size 2)	10	WXES213
WXES113	WXES213	13A single switched, single pole	10	WXES113S
		13A twin switched (size 2), single pole	10	WXES213S
		13A single switched with neon, single pole	10	WXES113N
WXES113S	WXES213S	13A twin switched with neon (size 2), single pole	10	WXES213N
WXES113SDP	WXES213SDP	13A single switched, double pole	10	WXES113SDP
		13A twin switched (size 2), double pole	10	WXES213SDP
WXES113N	WXES213N			





Dust preventive sticker





- * Socket are supplied with free dust damage prevention sticker to give additional protection during installation.
- * Sockets with red rocker are also available/ surcharge applies.

stylea
15A and 16A socket outlets

- Complies with BS 546 SS 472 IEC 60884 (for WXES116/ 116S) IEC 60884-1 (for WXES116IS)
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
L, N: 2 X 4.0 mm²
E: 3 X 2.5 mm²
- Integral rocker design of switched sockets provides clear red 'on' indication
- Material: Polycarbonate


		Description	Pack qty.	Cat. Ref.
		Socket outlets 15A round pin unswitched	10	WXES115
		15A round pin switched	10	WXES115S
WXES115	WXES115S	German style sockets 16A German style (without shutter)	10	WXES116
		16A German style (with shutter)	10	WXES116S
WXES116	WXES116IS	Universal sockets 16A 3 pin switched universal	10	WXES116IS
WXES116S				

- Complies with BS 1363-4
- Cable clamp accommodates up to 2.5 mm² flexible cord
- Supplied with M3.5 x 25 mm long fixing screws
- All switched units are double pole
- Capacity of each terminal:
L, N: 3 X 4.0 mm²
E: 2 X 4.0 mm²
- All units fitted with a 13A fuse link to BS 1362, can be supplied with 2A, 5A fuse link.
- Material: polycarbonate
- Optional flex outlet - for choice of use

		Description	Pack qty.	Cat. Ref.
		Fused connection units 13A fused with flex outlet	10	WXER13
		13A fused with neon and flex outlet	10	WXER13N
		13A switched fused with flex outlet	10	WXER13S
		13A switched fused with neon and flex outlet	10	WXER13SN
		2A fused with flex outlet	10	WXER132
		2A fused with neon and flex outlet	10	WXER13N2
		2A switched fused with flex outlet	10	WXER13S2
		2A switched fused with neon and flex outlet	10	WXER13SN2
		5A fused with flex outlet	10	WXER135
		5A fused with neon and flex outlet	10	WXER13N5
		5A switched fused with flex outlet	10	WXER13S5
		5A switched fused with neon and flex outlet	10	WXER13SN5

stylea
connection unit

- Complies with BS 5733
- Supplied with M3.5 x 25 mm long fixing screws
- Capacity of each terminal:
L, N: 2 x 6.0 mm²
E: 2 x 6.0 mm²
- Material: polycarbonate

		Description	Pack qty.	Cat. Ref.
		Connection unit 25A connection unit with flex outlet	10	WXER25